

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2021/0170097 A1 Kamen et al.

Jun. 10, 2021 (43) **Pub. Date:**

(54) SYSTEM AND METHODS FOR FLUID DELIVERY

(71) Applicant: **DEKA Products Limited Partnership**,

Manchester, NH (US)

(72) Inventors: Dean Kamen, Bedford, NH (US); John

M. Kerwin, Manchester, NH (US); Larry B. Gray, Merrimack, NH (US); Marc A. Mandro, Bow, NH (US); David Blumberg, Deerfield, NH (US)

(21) Appl. No.: 16/998,741

(22) Filed: Aug. 20, 2020

Related U.S. Application Data

- (63) Continuation of application No. 15/871,571, filed on Jan. 15, 2018, now Pat. No. 10,751,467, which is a continuation of application No. 14/336,530, filed on Jul. 21, 2014, now Pat. No. 9,867,930, which is a continuation of application No. 12/560,106, filed on Sep. 15, 2009, now Pat. No. 8,784,364.
- (60) Provisional application No. 61/097,021, filed on Sep. 15, 2008, provisional application No. 61/101,053, filed on Sep. 29, 2008, provisional application No. 61/101,077, filed on Sep. 29, 2008, provisional application No. 61/101,105, filed on Sep. 29, 2008, provisional application No. 61/101,115, filed on Sep. 29, 2008, provisional application No. 61/141,996, filed on Dec. 31, 2008, provisional application No. 61/141,781, filed on Dec. 31, 2008.

Publication Classification

(51)	Int. Cl.	
	A61M 5/142	(2006.01)
	A61M 5/172	(2006.01)
	A61M 5/168	(2006.01)
	G08C 17/02	(2006.01)
	G05D 7/06	(2006.01)

G01F 11/08	(2006.01)
H04B 7/26	(2006.01)
A61M 5/145	(2006.01)

(52) U.S. Cl.

CPC A61M 5/14244 (2013.01); Y10T 29/49828 (2015.01); A61M 5/142 (2013.01); A61M 5/16886 (2013.01); G08C 17/02 (2013.01); G05D 7/0647 (2013.01); A61M 5/16809 (2013.01); G05D 7/0676 (2013.01); A61M 5/14248 (2013.01); A61M 5/14224 (2013.01); G01F 11/086 (2013.01); H04B 7/2609 (2013.01); A61M 5/1723 (2013.01); A61M 5/14586 (2013.01); A61M 2005/16863 (2013.01); A61M 2205/8237 (2013.01); A61M 2209/045 (2013.01); A61M 2005/14268 (2013.01); A61M 2205/0266 (2013.01); A61M 2205/332 (2013.01); A61M 2205/50 (2013.01); A61M 2205/3546 (2013.01); A61M 2206/22 (2013.01); A61M 2205/3375 (2013.01); A61M 2205/3368 (2013.01); A61M 2230/201 (2013.01); A61M 2205/3331 (2013.01); Y10T 29/49236 (2015.01); Y10T 29/49826 (2015.01); Y10T 29/49412 (2015.01); A61M 2205/3576 (2013.01); A61M 2205/0294 (2013.01); A61M 2205/52 (2013.01); Y10T 29/494 (2015.01); A61M 2205/18 (2013.01); A61M 5/172 (2013.01)

(57)ABSTRACT

A system for at least partial closed-loop control of a medical condition is disclosed. The system includes at least one medical fluid pump. The medical fluid pump including a sensor for determining the volume of fluid pumped by the pump. Also, at least one continuous analyte monitor, and a controller. The controller is in communication with the medical fluid pump and the at least one continuous analyte monitor. The controller includes a processor. The processor includes instructions for delivery of medical fluid based at least on data received from the at least one continuous analyte monitor.

